

Description

WS 3915 G is a high efficiency coolant specifically formulated and recommended for use in the following applications on Welding and Cutting Torches of all types, even in the most demanding working conditions, increases the life of consumables (torch, hoses, pumps).

Properties

- Low viscosity, non-toxic, non-flammable, no Danger pictograms.
- Excellent cooling extending the life of flares, ducts and pumps.
- Lubricates pump, gaskets and seals, prolonging preventive maintenance.
- Protects copper, brass, aluminium and steel from corrosion.
- Environmentally friendly.
- Non-hazardous for storage.

Applications

Torch Coolant specifically formulated and recommended for:

- MIG welding.
- TIG welding.
- LASER welding.
- LASER cutting.
- PLASMA welding.
- ROBOTIC welding.
- Spot welding.
- Any other welding system requiring a coolant.

Instructions of use

- Product ready for direct use, no dilution necessary.
- Do not mix with automotive coolants.

Technical data

Property	Specification/Method	Value
Reference	- - - - -	WS 3915 G
Aspect	- - - - -	Liquid
Colour	- - - - -	Transparent
Density at 20°C	- - - - -	1.01 Kg/l
Conductivity	micros/cm 20°C	0
Minimum temperature	- - - - -	-10°C
Maximum temperature	- - - - -	102°C
Boiling point	- - - - -	102°C



Whale Spray S.L.

Pl. Ametlla Park.
 L'Ametlla del Vallès.
 08480 · Barcelona, Spain.
 T. : +34 93 882 77 12
 whalespray@whalespray.com

All data contained in this document are based on experience and laboratory tests. The wide range of equipment and environmental conditions, as well as unforeseen human factors, may affect the application results to a greater or lesser extent. For this reason, we recommend that you check the compatibility of the product before use. This information is based on reliable experience, but is only indicative.